



### FLOWave SAW flowmeter

- No obstacles inside the measuring tube, compact, lightweight and low energy consumption
- Conforms to hygienic requirements, CIP/SIP compatible
- Ideal for liquids with low or no conductivity
- Digital communication, parameterisation via Communicator, display
- Optional: ATEX/IECEX certification, II 3G/D

Product variants described in the data sheet may differ from the product presentation and description.

#### Can be combined with

	<b>Type 8802</b> ELEMENT continuous control valve systems - overview	▶
	<b>Type 8619</b> multiCELL - Multi-channel and multi-function transmitter/controller	▶
	<b>Type 8647</b> AirLINE SP – electro-pneumatic automation system	▶
	<b>Type ME43</b> Fieldbus gateway	▶

#### Type description

The Type 8098 flowmeter is part of the FLOWave product range. It is based on SAW (Surface Acoustic Waves) technology and is mainly designed for applications with the highest hygienic demands. This is achieved by using:

- suitable stainless steel materials
- a measuring tube free of any wetted parts except for the actual tube
- the ideal outer hygienic design.

FLOWave offers a range of integrated functions, including the advantages of flexibility, ease of cleaning, compact dimensions, lightweight, easy installation and handling, and is compliant with numerous standards.

Optimal measurement results can be achieved with homogeneous liquids, free of air and solid particles. For liquids with high viscosity, an integrated viscosity compensation can be activated. Gas and steam cannot be measured; however, their flow does not have any negative effect on the device or its operation and other liquids flowing through afterwards are measured correctly as before.

Beside volume flow, a density measurement optional feature is available. With this option, the mass flow is calculated based on volume flow and density measurements.

Special functions derived from further process values (differentiation factor (DF), acoustic transmission factor) offer additional information about the particular liquid in use (for details, see chapter **“7.2. Special functions” on page 30**).

DTS 1000270652 EN Version: U Status: RL (released | freigegeben | valide) printed: 12.07.2023



## Table of contents

<b>1. General technical data</b>	<b>4</b>
1.1. About the device.....	4
1.2. All variants.....	4
1.3. FLOWave L flowmeter.....	9
With or without industrial communication .....	9
With industrial communication (Ethernet variant) .....	11
1.4. FLOWave S flowmeter .....	13
<b>2. Approvals</b>	<b>15</b>
2.1. Certifications .....	15
2.2. Certificates .....	16
2.3. Pressure equipment directive .....	16
Device used on a pipe .....	16
<b>3. Materials</b>	<b>16</b>
3.1. Bürkert resistApp .....	16
3.2. Material specifications .....	17
FLOWave L flowmeter without industrial communication .....	17
FLOWave L flowmeter with industrial communication.....	18
FLOWave S flowmeter .....	19
<b>4. Dimensions</b>	<b>20</b>
4.1. Transmitter of the FLOWave L flowmeter without industrial communication .....	20
4.2. Transmitter of the FLOWave L flowmeter with industrial communication (Ethernet variant).....	20
4.3. Transmitter of the FLOWave S flowmeter .....	20
4.4. Flowmeter with clamp process connection .....	21
4.5. Flowmeter with aseptic collar flange (BF) .....	23
4.6. Flowmeter with aseptic collar clamp (BKS) .....	24
4.7. Flowmeter with thread connection.....	25
<b>5. Performance specifications</b>	<b>25</b>
5.1. Medium temperature diagram.....	25
5.2. Measurement deviation table.....	26
5.3. Refresh time table .....	26
<b>6. Product installation</b>	<b>27</b>
6.1. Installation notes.....	27
6.2. Selection of the nominal diameter .....	27
6.3. Mounting options .....	28
FLOWave L flowmeter.....	28
FLOWave S flowmeter .....	28
<b>7. Product operation</b>	<b>29</b>
7.1. Measuring principle.....	29
7.2. Special functions.....	30
<b>8. Product design and assembly</b>	<b>30</b>
8.1. Product assembly .....	30
<b>9. Product accessories</b>	<b>31</b>

<b>10. Ordering information</b>	<b>31</b>
10.1. Bürkert eShop .....	31
10.2. Recommendation regarding product selection.....	31
10.3. Bürkert product filter .....	32
10.4. Bürkert 3D Model.....	32
10.5. Ordering chart FLOWave L flowmeter with or without industrial communication .....	33
Clamp process connection acc. to DIN 32676 series A for pipe acc. to DIN 11866 series A (DIN 11850) .....	33
Clamp process connection acc. to DIN 32676 series B for pipe acc. to DIN 11866 series B (ISO 1127) .....	34
Clamp process connection acc. to DIN 32676 series C for pipe acc. to DIN 11866 series C (ASME BPE).....	35
Thread process connection acc. to DIN 11851 series A for pipe acc. to DIN 11866 series A (DIN 11850) .....	36
10.6. Ordering chart FLOWave S flowmeter .....	37
Clamp process connection acc. to DIN 32676 series A for pipe acc. to DIN 11866 series A (DIN 11850) .....	37
Clamp process connection acc. to DIN 32676 series B for pipe acc. to DIN 11866 series B (ISO 1127) .....	38
Clamp process connection acc. to DIN 32676 series C for pipe acc. to DIN 11866 series C (ASME BPE).....	39
Thread process connection acc. to DIN 11851 series A for pipe acc. to DIN 11866 series A (DIN 11850) .....	40
10.7. Ordering chart accessories.....	41
<b>11. Product Enquiry Form - FLOWave SAW flowmeter</b>	<b>42</b>

## 1. General technical data

### 1.1. About the device

The flowmeter Type 8098 consists of:

- either a flow sensor Type S097 and a FLOWave L transmitter (variant FLOWave L flowmeter), which is available with or without industrial communication (the FLOWave L variant with industrial communication, recognisable by the two M12 circular female connectors and the M12 circular male connector, is called the Ethernet variant.)



- or a flow sensor Type S097 and a FLOWave S transmitter (variant FLOWave S flowmeter)



### 1.2. All variants

#### Note:

- The following data applies to all variants mentioned above.
- In the following table, the term “full scale” refers to full scale of volume flow rate, i.e. the flow rate corresponding to 10 m/s flow velocity.

#### Product properties

##### Material

Please make sure the device materials are compatible with the fluid you are using. Detailed information can be found in chapter “[3.1. Bürkert resistApp](#)” on page 16.

Detailed information on the materials can be found in chapter “[3.2. Material specifications](#)” on page 17.

##### Non wetted parts

- |                |   |
|----------------|---|
| Sensor housing | <ul style="list-style-type: none"> <li>• For sensor with process connection <math>\leq</math> DN 50/2": stainless steel 304/1.4301</li> <li>• For sensor with process connection <math>&gt;</math> DN 50/2": stainless steel 316L/1.4435</li> </ul> |
|----------------|---|

##### Wetted parts

Measurement tube and process connection	Stainless steel 316L/1.4435 with low delta ferrite content
---	--

##### Surface quality

- |                                  |  |
|----------------------------------|--|
| Measurement tube (inner surface) | <ul style="list-style-type: none"> <li>• Ra <math>&lt;</math> 0.8 <math>\mu</math>m (30 <math>\mu</math>in.) or</li> <li>• Ra <math>&lt;</math> 0.4 <math>\mu</math>m (15 <math>\mu</math>in.) (electro-polished) according to ISO 4288</li> </ul> |
|----------------------------------|--|

Dimensions	Detailed information can be found in chapter “ <a href="#">4. Dimensions</a> ” on page 20.
------------	--

Measuring element	Interdigital transducers
-------------------	--------------------------

Measuring principle	Based on SAW (Surface Acoustic Waves)
---------------------	---------------------------------------

### Measuring range

Volume flow rate measurement	0...1.7 m <sup>3</sup> /h up to 0...200 m <sup>3</sup> /h Detailed information can be found in chapter <a href="#">“10.5. Ordering chart FLOWave L flowmeter with or without industrial communication” on page 33</a> or <a href="#">“10.6. Ordering chart FLOWave S flowmeter” on page 37</a> .
Density measurement <sup>1)</sup>	0.8...1.3 g/cm <sup>3</sup> (inactive by default, selectable upon request)
Mass flow rate measurement <sup>1)</sup>	0...1 360 kg/h up to 0...260 000 kg/h (inactive by default, selectable upon request)
Temperature measurement	-20...+140 °C (-4...+284 °F)
Special function	Active by default, deselectable upon request. <ul style="list-style-type: none"> <li>• ATF: acoustic transmission factor</li> <li>• DF: differentiation factor</li> </ul> Detailed information can be found in chapter <a href="#">“7.2. Special functions” on page 30</a> .

### Performance data

#### Volume flow rate measurement

Under reference conditions i.e. measuring fluid = water free from gas bubbles and solids, ambient and water temperature = 23 °C ± 1 °C (73.4 °F ± 1.8 F), and short refresh time, while maintaining turbulent or laminar flow profile, with the minimum inlet (40 x DN) and outlet (1 x DN) distances and the appropriate internal diameter of the pipes. Deviation from reference conditions can be adjusted through the use of a built-in correction K factor adjustment or Teach-in Procedure.

Measurement deviation	<ul style="list-style-type: none"> <li>• From 10 % of full scale up to full scale: ±0.4 % of the measured value</li> <li>• From 1 % of full scale up to 10 % of full scale: ±0.08 % of full scale</li> </ul> Detailed information can be found in chapter <a href="#">“5.2. Measurement deviation table” on page 26</a> .
Repeatability	<ul style="list-style-type: none"> <li>• From 10 % of full scale up to full scale: ±0.2 % of the measured value</li> <li>• From 1 % of full scale up to 10 % of full scale: ±0.04 % of full scale</li> </ul>
Refresh time	Selectable between very short, short and long Detailed information can be found in chapter <a href="#">“5.3. Refresh time table” on page 26</a> .

#### Density measurement

As an option<sup>1)</sup>

Under reference conditions i.e. measuring fluid = water free from gas bubbles and solids, ambient and water temperature = 23 °C ± 1 °C (73.4 °F ± 1.8 F). Deviations from reference conditions, especially exposure of the device to temperatures above 90 °C can be adjusted through the use of a built in adjustment procedure (see [user manual Type 8098](#) ▶).

Measurement deviation	<ul style="list-style-type: none"> <li>• Standard product adjustment: ±2 % of the measured value</li> <li>• After Teach-In: ±1 % of the measured value (at teach-in density value)</li> </ul>
Repeatability	±1 % of the measured value
Refresh time	Selectable between very short, short and long Detailed information can be found in chapter <a href="#">“5.3. Refresh time table” on page 26</a> .

#### Mass flow rate measurement

As an option<sup>1)</sup>

Under reference conditions i.e. measuring fluid = water free from gas bubbles and solids, ambient and water temperature = 23 °C ± 1 °C (73.4 °F ± 1.8 F), and short refresh time, while maintaining turbulent or laminar flow profile, with the minimum inlet (40 x DN) and outlet (1 x DN) distances and the appropriate internal diameter of the pipes. Deviation from reference conditions, can be adjusted through the use of a built-in correction K factor adjustment or Teach-in Procedure.

Measurement deviation	<ul style="list-style-type: none"> <li>• Standard K-factor: <ul style="list-style-type: none"> <li>– From 10 % of full scale up to full scale: ±2.4 % of the measured value</li> <li>– From 1 % of full scale up to 10 % of full scale: ±(2 % of the measured value + 0.08 % of full scale)</li> </ul> </li> <li>• After Teach-In: <ul style="list-style-type: none"> <li>– From 10 % of full scale up to full scale: ±1.4 % of the measured value at teach-in density and mass flow rate values</li> <li>– From 1 % of full scale up to 10 % of full scale: ±(1 % of the measured value + 0.08 % of full scale) at teach-in density and mass flow rate values</li> </ul> </li> </ul> Detailed information can be found in chapter <a href="#">“5.2. Measurement deviation table” on page 26</a> .
Repeatability	<ul style="list-style-type: none"> <li>• From 10 % of full scale up to full scale: ±1.2 % of the measured value</li> <li>• From 1 % of full scale up to 10 % of full scale: ±(1 % of the measured value + 0.04 % of full scale)</li> </ul>
Refresh time	Selectable between very short, short and long Detailed information can be found in chapter <a href="#">“5.3. Refresh time table” on page 26</a> .

**Temperature measurement**

Measurement deviation	<ul style="list-style-type: none"> <li>For <math>T^{\circ} \leq 100^{\circ}\text{C}</math> (<math>+212^{\circ}\text{F}</math>): <math>\pm 1^{\circ}\text{C}</math> (<math>+1.8^{\circ}\text{F}</math>)</li> <li>For <math>100^{\circ}\text{C}</math> (<math>+212^{\circ}\text{F}</math>) <math>&lt; T^{\circ} &lt; 140^{\circ}\text{C}</math> (<math>+284^{\circ}\text{F}</math>): <math>\pm 1.5\%</math></li> </ul>
Refresh time	Approx. 0.1 s

**Electrical data**

Operating voltage	<ul style="list-style-type: none"> <li>12...35 V DC filtered and regulated</li> <li>Tolerance: <math>\pm 10\%</math></li> <li>Connection to main supply: permanent (through external SELV (Safety Extra Low Voltage) and LPS (Limited Power Source) power supply)</li> </ul>
Power source (not supplied)	Limited power source according to UL/EN 60950-1 standards or limited energy circuit according to UL/EN 61010-1 §9.4
DC reverse polarity protection	Yes

**Voltage supply cable**

For cable gland	<ul style="list-style-type: none"> <li>0.2...1.5 mm<sup>2</sup> cross-section</li> <li>In nickel plated brass: <ul style="list-style-type: none"> <li>Cable with maximum operating temperature greater than <math>+80^{\circ}\text{C}</math> (<math>+176^{\circ}\text{F}</math>)</li> <li>5...14 mm diameter, shielded cable</li> </ul> </li> <li>In stainless steel: <ul style="list-style-type: none"> <li>Cable with maximum operating temperature greater than <math>+80^{\circ}\text{C}</math> (<math>+176^{\circ}\text{F}</math>)</li> <li>6...12 mm diameter, shielded cable</li> </ul> </li> </ul>
For 5-pin M12 circular male connector (A-coded)	<ul style="list-style-type: none"> <li>Cable with maximum operating temperature greater than <math>+80^{\circ}\text{C}</math> (<math>+176^{\circ}\text{F}</math>)</li> <li>3...6.5 mm diameter, shielded cable,</li> <li>0.75 mm<sup>2</sup> cross-section to connect to 5-pin M12 female connector (A-coded, not supplied)</li> </ul>
For 4-pin M12 circular female connector (D-coded)	<ul style="list-style-type: none"> <li>Cable with maximum operating temperature greater than <math>+80^{\circ}\text{C}</math> (<math>+176^{\circ}\text{F}</math>)</li> <li>5e / CAT-5 min. category, 100 m max. length, shielded conductor with minimum STP</li> </ul>

**Medium data**

Fluid	<p>Non-dangerous liquids complying with article 4, §1 of 2014/68/EU directive. Detailed information can be found in chapter <b>"2.3. Pressure equipment directive"</b> on page 16.</p> <p>By default the FLOWave flowmeter is set for a fluid with a sound velocity<sup>2)</sup></p> <ul style="list-style-type: none"> <li>between 1000 m/s and 2000 m/s for process connection DN 08, <math>\frac{3}{8}</math>" and <math>\frac{1}{2}</math>"</li> <li>between 800 m/s and 2300 m/s for process connection DN <math>\geq 15</math> or <math>\geq \frac{3}{4}</math>"</li> </ul>
Fluid temperature	<ul style="list-style-type: none"> <li><math>-20...+110^{\circ}\text{C}</math> (<math>-4...+230^{\circ}\text{F}</math>). The maximum fluid temperature can be restricted by the ambient operating temperature.</li> <li>Max. conditions for sterilisation process: up to <math>+140^{\circ}\text{C}</math> (<math>+284^{\circ}\text{F}</math>) (<math>+130^{\circ}\text{C}</math> (<math>+266^{\circ}\text{F}</math>) for ATEX/IECEx variant) for max. 60 min</li> <li>Maximum temperature gradient: <math>10^{\circ}\text{C/s}</math> (<math>18^{\circ}\text{F/s}</math>) (measured by the integrated sensor on the device)</li> </ul>

**Fluid pressure (max.)**

DN / Pipe standard	DIN 11850	ISO 1127	ASME BPE	SMS 3008
DN 08, $\frac{3}{8}$ ", $\frac{1}{2}$ "	PN 25	PN 25	PN 25	–
DN 15, $\frac{3}{4}$ ", DN 25, 1", $1\frac{1}{2}$ "	PN 25	PN 25	PN 25	PN 25
DN 40	PN 25	PN 16	–	PN 25
DN 50, 2"	PN 16	PN 16	PN 16	PN 16
DN 65, $2\frac{1}{2}$ ", DN 80, 3"	PN 10	PN 10	PN 10	–

**Process/Pipe connection & communication****Process connection size / pipe size<sup>3)</sup> according to**

DIN 32676 series A / DIN 11850	Clamp: DN 08, DN 15, DN 25, DN 40, DN 50, DN 65 and DN 80
DIN 32676 series B / ISO 1127	Clamp: DN 08, DN 15, DN 25, DN 40, DN 50, DN 65 and DN 80
DIN 32676 series C / ASME BPE	Clamp: 3/8", 1/2", 3/4", 1", 1 1/2", 2", 2 1/2" and 3"
DIN 11864-2 form A series A / DIN 11850	Aseptic collar flange (BF) <sup>4)</sup> : DN 15, DN 25, DN 40, DN 50, DN 65 and DN 80
DIN 11864-2 form A series B / ISO 1127	Aseptic collar flange (BF) <sup>4)</sup> : DN 08, DN 15, DN 25, DN 40, DN 50, DN 65 and DN 80
DIN 11864-2 form A series C / ASME BPE	Aseptic collar flange (BF) <sup>4)</sup> : 1/2", 3/4", 1", 1 1/2" and 2"
DIN 11864-3 form A series A / DIN 11850	Aseptic collar clamp (BKS) <sup>4)</sup> : DN 15, DN 25, DN 40 and DN 50
DIN 11864-3 form A series B / ISO 1127	Aseptic collar clamp (BKS) <sup>4)</sup> : DN 08, DN 15, DN 25, DN 40 and DN 50
DIN 11864-3 form A series C / ASME BPE	Aseptic collar clamp (BKS) <sup>4)</sup> : 1/2", 3/4", 1", 1 1/2" and 2"
SMS 3017 / SMS 3008	Clamp: DN 25, DN 40 and DN 50
DIN 11851 series A / DIN 11850	Thread: DN 65 and DN 80
Device status	LED light ring according to NAMUR NE 107

**Approvals and Certificates****Directives**

CE directive	The applied standards, which verify conformity with the EU Directives, can be found on the EU Type Examination Certificate and/or the EU Declaration of conformity (if applicable).
Pressure equipment directive	Complying with article 4, paragraph 1 of 2014/68/EU directive Detailed information on the pressure equipment directive can be found in chapter <b>"2.3. Pressure equipment directive"</b> on page 16.

Certification	<ul style="list-style-type: none"> <li>• EHEDG (Type EL CLASS I)<sup>5)</sup></li> <li>• 3A (28-06)</li> <li>• On request: <ul style="list-style-type: none"> <li>– UL-Listed for USA and Canada</li> <li>– ATEX/IECEX</li> </ul> </li> </ul>
Certificate	<ul style="list-style-type: none"> <li>• FDA declaration of conformity</li> <li>• Inspection certificate 3.1</li> <li>• Certification of compliance ASME BPE</li> <li>• Fluidic test report (test regarding volumetric flow rate or volume and mass flow rates, if density and mass flow rate option chosen)</li> <li>• On request: <ul style="list-style-type: none"> <li>– Calibration certificate (volumetric flow rate, volume and mass flow rates and density)</li> <li>– USP class VI declaration</li> <li>– ECR1935/2004 declaration</li> <li>– CRN 0C21751 declaration<sup>6)</sup></li> <li>– Test report 2.2</li> <li>– Certification of conformity for the surface quality DIN 4762, EN ISO 4287, EN ISO 4288</li> <li>– Certification of conformity for passivation and electro-polishing processes</li> <li>– MTBF (Mean Time Between Failures) manufacturer declaration</li> </ul> </li> </ul>

**Environment and installation****Ambient temperature**

Operation	Depends on the fluid temperature. Detailed information can be found in chapter <b>"5.1. Medium temperature diagram"</b> on page 25.
Storage	-20...+70 °C (-4...+158 °F)
Relative air humidity	≤ 85 %, without condensation
Height above sea level	Max. 2000 m
Operating condition	Continuous
Equipment mobility	Fixed device

Application range	Indoor and outdoor (protect the device against electromagnetic interference, ultraviolet rays and, when installed outdoors, against the effects of climatic conditions)
Degree of protection <sup>7.)</sup>	IP65, IP67 (according to IEC/EN 60529), NEMA 4X (according to NEMA250), if the product is wired and if the cable glands are tightened and the covers are screwed tight. Unused cable glands must be sealed with the stopper gaskets provided (mounted upon delivery of the product). An unused M12 fixed connector must be protected by the screwed plug.
Installation category	Category I according to UL/EN 61010-1
Pollution degree	Degree 2 according to UL/EN 61010-1

1.) Only for a flowmeter FLOWave with a process connection size of DN 08...DN 50 or ½"...2", pending for the other dimensions

2.) Customer specific setting on request. Please contact your Bürkert partners!

3.) Please refer to the dimension table of the sensor, see chapters "4.4. Flowmeter with clamp process connection" on page 21, "4.5. Flowmeter with aseptic collar flange (BF)" on page 23, "4.6. Flowmeter with aseptic collar clamp (BKS)" on page 24, and "4.7. Flowmeter with thread connection" on page 25.

4.) In German: BF = Bundflansch, BKS= Bundklemmstutzen

5.) The EHEDG compliance for :

- clamp connection according to DIN 32676 is only valid if used in combination with EHEDG-compliant gaskets from Combifit International B.V.

- threaded connection according to DIN 11851 is only valid if used in combination with EHEDG-compliant gaskets from

1. Kieselmann GmbH, Germany (ASEPTO-STAR k-flex upgrade gaskets) or

2. Siersema Componenten Service (S.K.S.) B.V. (Netherlands SKS gasket set DIN 11851 EHEDG with EPDM or FKM inner gasket)

6.) Only for a flowmeter with a process connection size of ¾"...2", pending for the other dimensions

7.) Not evaluated by UL, only IP64 is evaluated by the ATEX/IECEx notified/certification body.



### 1.3. FLOWave L flowmeter

The FLOWave L flowmeter is available in four variants of the transmitter:

- Stainless steel transmitter with nickel plated brass cable glands and M12 circular male connector
- Stainless steel transmitter with stainless steel cable glands and M12 circular male connector (full stainless steel variant)
- Stainless steel transmitter with stainless steel M12 circular female and male connectors and industrial communication (Ethernet variant)
- Stainless steel transmitter with stainless steel cable glands and M12 circular male connector (ATEX/IECEX variant).



#### With or without industrial communication

The following data applies to all variants (unless otherwise stated).

#### Product properties

##### Material

Detailed information on the materials can be found in chapter "3.2. Material specifications" on page 17.

##### Non wetted parts

Blind cover	Stainless steel 304/1.4301
Transmitter housing	Stainless steel 304/1.4301
Functional earth element	Cylinder screw, washer, washer spring in stainless steel A4 and blind rivet nut in stainless steel 1.4578/A4
Pressure compensating element	Diaphragm in ePTFE (expanded polytetrafluoroethylene), O-ring in silicone 60 Shore A, body in stainless steel
Display module	Float glass, stainless steel 304/1.4301 and EPDM (ethylene propylene diene monomer) seal
Seal	VMQ silicone (Methyl Vinyl Silicone)
M12 fixed connector and screwed plug	<ul style="list-style-type: none"> <li>• 4-pin M12 circular female connector:               <ul style="list-style-type: none"> <li>– Body in stainless steel 304L/1.4307, contact support in PBT GF30 (Polybutyleneterephthalate 30 % glass fibre reinforced) and seal in EPDM</li> </ul> </li> <li>• 5-pin M12 circular male connector:               <ul style="list-style-type: none"> <li>– Body in nickel plated brass and seal in NBR (nitrile butadiene rubber) or</li> <li>– Body in stainless steel 316L/1.4404 and seal in NBR or VMQ silicone</li> </ul> </li> </ul>
Cable gland	<ul style="list-style-type: none"> <li>• Body in nickel plated brass and seal in TPE (thermoplastic elastomer) or</li> <li>• Body in stainless steel 304L/1.4307 and seal in TPE (FDA-compliant) or</li> <li>• Body in stainless steel 316L/1.4404 and seal in EPDM</li> </ul>
Blind plug	Black POM (polyoxymethylene), PA6 or PA
Display	<ul style="list-style-type: none"> <li>• 2.4", monochrome graphic (240 × 160 pixels)</li> <li>• Languages: German, English, French</li> </ul>

Weight (approx. in kg)	DN 08, 3/8", 1/2"	DN 15, 3/4"	DN 25, 1"	DN 40, 1 1/2"	DN 50, 2"	DN 65, 2 1/2"	DN 80, 3"
Clamp	2.1	2	2.2	3	3.2	5.4	5.5
Flange	2.3	2.4	2.7	3.6	3.8	6	6.2
Thread (dairy thread)	–	–	–	–	–	5.7	6.1

#### Performance data

Frequency resolution	0.05 Hz over 0...2 000 Hz range
4...20 mA output uncertainty	±0.04 mA
4...20 mA output resolution	0.8 µA

**Electrical data**

Power consumption	Without any consumption of output <ul style="list-style-type: none"> <li>For device with 2 x M20 x 1.5 cable glands and 1 x 5-pin M12 circular male connector: max. 5 W</li> <li>For device with 2 x 4-pin M12 circular female connectors and 1 x 5-pin M12 male connector, Ethernet variant: max. 8 W</li> <li>For device with 2 x 4-pin M12 circular female connectors and 1 x 5-pin M12 male connector, Ethernet variant, with display module: max. 9 W</li> </ul>
-------------------	---

**Output**

Number of outputs	3 (1 digital, 1 analogue and 1 configurable: digital or analogue)
Digital output	<p>Overload information (through software diagnostics function)</p> <p>Transistor:</p> <ul style="list-style-type: none"> <li>Type: NPN or PNP (wiring dependent), open collector, galvanically isolated</li> <li>Operating modes: pulse (by default), On/Off, threshold, frequency (user configurable)</li> <li>10 kHz, 5...35 V DC, max. 700 mA, max. pulse duration: 2 s, selectable limits: <ul style="list-style-type: none"> <li>0.0001...10 000 pulses/litre or 0.0001...9 999.99 litres/pulse</li> <li>0.0001...10 000 pulses/kg or 0.0001...9 999.99 kg/pulse<sup>1.)</sup></li> </ul> </li> <li>Protected against polarity reversals of DC and overloads</li> </ul>
Analogue output	<p>Open loop detection (through software diagnostics function)</p> <p>Current:</p> <ul style="list-style-type: none"> <li>4...20 mA</li> <li>3.6 mA or 22 mA to indicate an error (only if 4...20 mA scale selected); galvanically isolated</li> <li>Max. loop impedance: 1 300 Ω at 35 V DC, 1 000 Ω at 30 V DC, 700 Ω at 24 V DC, 450 Ω at 18 V DC</li> </ul>

**Process/Pipe connection & communication**

Electrical connection	2 x M20 x 1.5 cable glands and 1 x 5-pin M12 circular male connector (A-coded) for non-Ethernet variants only
Data transfer	External communication through büS (Bürkert system bus, CANopen protocol)

**Environment and installation****Ambient temperature**

Operation	<ul style="list-style-type: none"> <li>For device with 2 x M20 x 1.5 cable glands and 1 x 5-pin M12 circular male connector: <ul style="list-style-type: none"> <li>-10...+70 °C (+14...+158 °F) or -10...+40 °C (+14...+104 °F) for ATEX/IECEX variant, if -20 °C (4 °F) ≤ fluid temperature ≤ 80 °C (176 °F),</li> <li>- At a fluid temperature &gt; 80 °C (176 °F), the maximum ambient temperature decreases linearly from 70 °C (158 °F) up to 40 °C (104 °F) or from 40 °C (104 °F) up to 30 °C (86 °F) for ATEX/IECEX variant. This means that at a fluid temperature of 80 °C (176 °F) the ambient temperature may be a maximum of 70 °C and at a fluid temperature of 140 °C (130 °C for the ATEX/IECEX variant) the ambient temperature may only be a maximum of 40 °C (30 °C for the ATEX/IECEX variant).</li> </ul> </li> <li>For device with 2 x 4-pin M12 circular female connectors and 1 x 5-pin M12 circular male connector, Ethernet variant: -10...+55 °C (+14...+131 °F)</li> </ul> <p>Detailed information can be found in chapter <b>"5.1. Medium temperature diagram"</b> on page 25.</p>
-----------	--

1.) Only if option density and mass flow is activated.

**With industrial communication (Ethernet variant)****Process/Pipe connection & communication**

Electrical connection 2 × 4-pin M12 circular female connectors (D-coded) and 1 × 5-pin M12 male connector (A-coded)

**Industrial Communication**

Supported network protocol

- Modbus TCP
- PROFINET
- EtherNet/IP
- EtherCAT

Light-emitting diode

- 2 Link/Act LEDs (green)
- 2 Link LEDs (yellow)

**Modbus TCP protocol**

Protocol Internet protocol, version 4 (IPv4)

Network topology

- Tree
- Star
- Line (open daisy chain)

IP configuration

- Static IP address
- Not supported: BOOTP (Bootstrap Protocol), DHCP (Dynamic Host Configuration)

Transmission speed 10 or 100 MBit/s

**PROFINET protocol**

PROFINET IO specification V2.3

Network topology

- Tree
- Star
- Ring (closed daisy chain)
- Line (open daisy chain)

Network management

- LLDP (Link Layer Discovery Protocol)
- SNMP V1 (Simple Network Management Protocol)
- MIB (Management Information Base)

IP configuration

- DCP (Discovery and Configuration Protocol)
- Manual (Device naming and IP setting)

Transmission speed 100 MBit/s full duplex

Maximum supported conformance class CC-B

Media Redundancy (for ring topology) MRP client is supported

GSDml file See **Device Description Files Type 8098** ▶ on the website in the Software chapter.

**EtherNet/IP protocol**

Protocol Internet protocol, version 4 (IPv4)

Network topology

- Tree
- Star
- Ring (closed daisy chain)
- Line (open daisy chain)
- Linear (open Daisy Chain)

IP configuration

- Static IP address
- BOOTP (Bootstrap Protocol)
- DHCP (Dynamic Host Configuration Protocol)

Transmission speed 10 or 100 MBit/s

Duplex mode Half duplex, full duplex, auto-negotiation

MDI mode (Medium Dependant Interface) Auto-MDIX

Predefined standard objects Identity, Message Router, Assembly, Connection Manager, DLR, QoS, TCP/IP Interface, EtherNet Link object

EDS file See **Device Description Files Type 8098** ▶ on the website in the Software chapter.

**EtherCAT protocol<sup>1.)</sup>**

Industrial Ethernet interface X1, X2	X1: EtherCAT IN, X2: EtherCAT OUT
Maximum number of cyclic input/output data	512 bytes in total
Maximum number of cyclic input data	1024 bytes
Maximum number of cyclic output data	1024 bytes
Acyclic communication (CoE)	<ul style="list-style-type: none"> <li>• SDO</li> <li>• SDO master-slave</li> <li>• SDO slave-slave (depends on master capacity)</li> </ul>
Type	Complex slave
Fieldbus Memory Management Unit (FMMU)	8
Sync Manager	4
Transmission speed	100 Mbit/s

**Approvals and Certificates**

Certification	<ul style="list-style-type: none"> <li>• PROFINET</li> <li>• EtherNet/IP</li> </ul>
---------------	---

1.) EtherCAT® is a registered trademark and patented technology, licensed by Beckhoff Automation GmbH.

### 1.4. FLOWave S flowmeter

The FLOWave S flowmeter is available in four variants of the transmitter:

- Stainless steel transmitter without output and with stainless steel 5-pin M12 circular male connector
- Stainless steel transmitter with 2 configurable outputs (DO/AO) and stainless steel 8-pin M12 circular male connector
- Stainless steel transmitter without output and with stainless steel 5-pin M12 circular male connector (ATEX/IECEX variant)
- Stainless steel transmitter with 2 configurable outputs (DO/AO) and stainless steel 8-pin M12 circular male connector (ATEX/IECEX variant)



#### Product properties

##### Material

Detailed information on the materials can be found in chapter “3.2. Material specifications” on page 17.

##### Non wetted parts

Cover	Stainless steel 304/1.4301
Light guide	PC (Polycarbonate) and O-ring in EPDM (Ethylene Propylene Diene Monomer)
Transmitter housing	Stainless steel 304/1.4301
Functional earth element	Cylinder screw, washer, washer spring in stainless steel A4 and jumper of the ground terminal in stainless steel 304L
Seal	Between sensor and transmitter: VMQ silicone (Methyl Vinyl Silicone)
M12 fixed connector and screwed plug	5- or 8-pin M12 circular male connector: stainless steel 316L/1.4404 or 303/1.4305 and with seal in EPDM

Weight (approx. in kg)	DN 08, 3/8", 1/2"	DN 15, 3/4"	DN 25, 1"	DN 40, 1 1/2"	DN 50, 2"	DN 65, 2 1/2"	DN 80, 3"
Clamp	1.7	1.6	1.8	2.6	2.8	5.0	5.1
Flange	1.9	2.0	2.3	3.2	3.4	5.6	5.8
Thread (dairy thread)	–	–	–	–	–	5.3	5.7

##### Electrical data

Power consumption	<ul style="list-style-type: none"> <li>• For device without output: max. 2.5 W</li> <li>• For device with 2 outputs (DO/AO): max. 5 W</li> </ul>
-------------------	--

##### Output

Number of outputs	<b>Only for device with 8-pin M12 circular male connector</b> 2, each configurable as digital or analogue output
Digital output	Overload information (through software diagnostics function) Transistor: <ul style="list-style-type: none"> <li>• Type: NPN or PNP (wiring dependent), open collector, galvanically isolated</li> <li>• Operating modes: pulse (by default), On/Off, threshold, frequency (user configurable)</li> <li>• 10 kHz, 5...35 V DC, max. 700 mA, max. pulse duration: 2 s, selectable limits: <ul style="list-style-type: none"> <li>– 0.0001...10 000 pulses/litre or 0.0001...9 999.99 litres/pulse</li> <li>– 0.0001...10 000 pulses/kg or 0.0001...9 999.99 kg/pulse<sup>1)</sup></li> </ul> </li> <li>• Protected against polarity reversals of DC and overloads</li> </ul>
Analogue output	Open loop detection (through software diagnostics function) Current: <ul style="list-style-type: none"> <li>• 4...20 mA</li> <li>• 3.6 mA or 22 mA to indicate an error (only if 4...20 mA scale selected); galvanically isolated</li> <li>• Max. loop impedance: 1300 Ω at 35 V DC, 1000 Ω at 30 V DC, 700 Ω at 24 V DC, 450 Ω at 18 V DC</li> </ul>

##### Process/Pipe connection & communication

Electrical connection	<ul style="list-style-type: none"> <li>• 1 × 5-pin M12 circular male connector (A-coded) for device without output</li> <li>• 1 × 8-pin M12 circular male connector (A-coded) for device with 2 outputs</li> </ul>
-----------------------	--

## Data transfer

- Device without output: external communication through bÜS (Bürkert system bus, CANopen protocol)
- Device with 2 outputs: bÜS connection only to the Bürkert Communicator for configuration and software update of the device. Due to the missing CAN shield the conventional bÜS/CANopen communication is not recommended.

### Environment and installation

#### Ambient temperature

## Operation

- -10...+70 °C (+14...+158 °F) if -20 °C (4 °F) ≤ fluid temperature ≤ 80 °C (176 °F) or for ATEX/IECEX variant, -10...+60 °C (+14...+140 °F) if -20 °C (4 °F) ≤ fluid temperature ≤ 100 °C (212 °F)
- At a fluid temperature >80 °C (176 °F), the maximum ambient temperature decreases linearly from 70 °C (158 °F) up to 40 °C (104 °F).  
This means that at a fluid temperature of 80 °C (176 °F) the ambient temperature may be a maximum of 70 °C (158 °F) and at a fluid temperature of 140 °C (284 °F) the ambient temperature may only be a maximum of 40 °C (104 °F).  
or for ATEX/IECEX variant, at a fluid temperature >100 °C (212 °F), the maximum ambient temperature decreases linearly from 60 °C (140 °F) up to 45 °C (136 °F).  
This means that at a fluid temperature of 100 °C (212 °F) the ambient temperature may be a maximum of 60 °C (140 °F) and at a fluid temperature of 130 °C (266 °F) the ambient temperature may only be a maximum of 45 °C (136 °F)

Detailed information can be found in chapter **“5.1. Medium temperature diagram”** on page **25**.








1.) Only if option density measurement and mass flow rate measurement is activated

## 2. Approvals

### 2.1. Certifications

**Note:**


- The certification listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variant of the devices can be supplied with the certification below.

Certification	Description				
	<p><b>EHEDG (Type EL - CLASS I)</b> The EHEDG compliance is only valid</p> <ul style="list-style-type: none"> <li>• if the flowmeter with clamp connection according to DIN 32676 is used in combination with gaskets from Combifit International B.V.</li> <li>• if the flowmeter with threaded connection according to DIN 11851 is used in combination with gaskets from               <ul style="list-style-type: none"> <li>– Kieselmann GmbH, Germany (ASEPTO-STAR k-flex upgrade gaskets) or</li> <li>– Siersema Componenten Service (S.K.S.) B.V. (Netherlands SKS gasket set DIN 11851 EHEDG with EPDM or FKM inner gasket)</li> </ul> </li> </ul>				
	<p><b>3-A Sanitary Standards</b> The Type 8098 meets sanitary standards for design and fabrication. Certificate authorization number: 1178</p>				
	<p><b>UL-Listed for USA and Canada</b> The products are UL-listed and also comply with the following standards:</p> <ul style="list-style-type: none"> <li>• UL 61010-1</li> <li>• CAN/CSA-C22.2 No.61010-1</li> </ul> <p>Certificate number: 2017-10-27-E237737</p>				
 	<p><b>Explosion proof</b> As Category 3 device suitable for zone 2/22 (optional)</p> <table border="1"> <thead> <tr> <th>FLOWave L flowmeter</th> <th>FLOWave S flowmeter</th> </tr> </thead> <tbody> <tr> <td> <p><b>ATEX</b></p> <ul style="list-style-type: none"> <li>• II 3G Ex ec IIC T4 Gc</li> <li>• II 3D Ex tc IIIC T110 °C Dc or T130 °C Dc</li> </ul> <p><b>IECEX</b></p> <ul style="list-style-type: none"> <li>• Ex ec IIC T4 Gc</li> <li>• Ex tc IIIC T110 °C Dc or T130 °C Dc</li> </ul> </td> <td> <p><b>ATEX</b></p> <ul style="list-style-type: none"> <li>• II 3G Ex ec IIC T4 Gc</li> <li>• II 3D Ex tc IIIC T130 °C Dc</li> </ul> <p><b>IECEX</b></p> <ul style="list-style-type: none"> <li>• Ex ec IIC T4 Gc</li> <li>• Ex tc IIIC T130 °C Dc</li> </ul> </td> </tr> </tbody> </table> <p>Measures to comply with ATEX/IECEX requirements: refer to the</p> <ul style="list-style-type: none"> <li>• <b>Supplement Type 8098 FLOWave L   ATEX/IECEX Variant</b> ▶ or</li> <li>• <b>Supplement Type 8098 FLOWave S   ATEX/IECEX Variant</b> ▶</li> </ul> <p>under user manual. The Ex. certification is only valid if the Bürkert device is used as described in the supplement ATEX/IECEX. If unauthorized changes are made to the device, the Ex. certification becomes invalid.</p>	FLOWave L flowmeter	FLOWave S flowmeter	<p><b>ATEX</b></p> <ul style="list-style-type: none"> <li>• II 3G Ex ec IIC T4 Gc</li> <li>• II 3D Ex tc IIIC T110 °C Dc or T130 °C Dc</li> </ul> <p><b>IECEX</b></p> <ul style="list-style-type: none"> <li>• Ex ec IIC T4 Gc</li> <li>• Ex tc IIIC T110 °C Dc or T130 °C Dc</li> </ul>	<p><b>ATEX</b></p> <ul style="list-style-type: none"> <li>• II 3G Ex ec IIC T4 Gc</li> <li>• II 3D Ex tc IIIC T130 °C Dc</li> </ul> <p><b>IECEX</b></p> <ul style="list-style-type: none"> <li>• Ex ec IIC T4 Gc</li> <li>• Ex tc IIIC T130 °C Dc</li> </ul>
FLOWave L flowmeter	FLOWave S flowmeter				
<p><b>ATEX</b></p> <ul style="list-style-type: none"> <li>• II 3G Ex ec IIC T4 Gc</li> <li>• II 3D Ex tc IIIC T110 °C Dc or T130 °C Dc</li> </ul> <p><b>IECEX</b></p> <ul style="list-style-type: none"> <li>• Ex ec IIC T4 Gc</li> <li>• Ex tc IIIC T110 °C Dc or T130 °C Dc</li> </ul>	<p><b>ATEX</b></p> <ul style="list-style-type: none"> <li>• II 3G Ex ec IIC T4 Gc</li> <li>• II 3D Ex tc IIIC T130 °C Dc</li> </ul> <p><b>IECEX</b></p> <ul style="list-style-type: none"> <li>• Ex ec IIC T4 Gc</li> <li>• Ex tc IIIC T130 °C Dc</li> </ul>				
	<p><b>PROFINET</b> Certificate number: Z12446</p>				
	<p><b>EtherNet/IP</b> Document number: 11839</p>				

## 2.2. Certificates

### Note:

- The certificate listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variant of the devices can be supplied with the certificate below.

Certificate	Description
FDA	<b>Food contact</b> The devices comply in their composition with the Code of Federal Regulations published by the FDA (Food and Drug Administration, USA).
 EtherCAT®	EtherCAT® is a registered trademark and patented technology, licensed by Beckhoff Automation GmbH.

## 2.3. Pressure equipment directive

The device conforms to article 4, paragraph 1 of the pressure equipment directive 2014/68/EU under the following conditions:

### Device used on a pipe


#### Note:

- The data in the table is independent of the chemical compatibility of the material and the fluid.
- PS = maximum admissible pressure (in bar), DN = nominal diameter of the pipe

Type of fluid	Conditions
Fluid group 1, article 4, paragraph 1.c.i	DN ≤ 25
Fluid group 2, article 4, paragraph 1.c.i	DN ≤ 32 or PS*DN ≤ 1000
Fluid group 1, article 4, paragraph 1.c.ii	DN ≤ 25 or PS*DN ≤ 2000
Fluid group 2, article 4, paragraph 1.c.ii	DN ≤ 200 or PS ≤ 10 or PS*DN ≤ 5000

## 3. Materials

### 3.1. Bürkert resistApp



#### Bürkert resistApp – Chemical Resistance Chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

[Start Chemical Resistance Check](#)




### 3.2. Material specifications

#### FLOWave L flowmeter without industrial communication

##### Note:

The following picture describes a device with 2 x M20 x 1.5 cable glands, 1 x 5-pin M12 circular male connector and clamp process connection.




No.	Element	Material
1	Blind cover	Stainless steel 304/1.4301
2	Display module	Float glass, stainless steel 304/1.4301
3	Multi-colour LED behind seal (used for e.g. to indicate the status of the product, based on the NAMUR NE 107 standard)	VMQ silicone
4	Transmitter housing	Stainless steel 304/1.4301
5	Cable gland (full stainless steel variant)	Body in stainless steel 304L/1.4307 and seal in TPE (according to FDA)
6a	Cable glands	Body in nickel plated brass and seal in TPE
6b	Cable glands (ATEX/IECEx variant)	Body in stainless steel 316L/1.4404 and seal in EPDM
6c	Blind plug (full stainless steel variant)	PA6
7a	Blind plug	Black POM
7b	Blind plug (ATEX/IECEx variant)	PA
7c	5-pin M12 circular male connector (wired to bus) with screwed plug	<ul style="list-style-type: none"> <li>Body in stainless steel 316L/1.4404 and seal in NBR (if equipped with 6a) or in VMQ silicone (if equipped with 6c) or</li> <li>Body in nickel plated brass and seal in NBR (if equipped with 6b)</li> </ul>
8	Functional earth	Cylinder screw, washer, washer spring in stainless steel A4 and blind rivet nut in stainless steel 1.4578/A4
9	Seal	VMQ silicone
10	Blind cover	Stainless steel 304/1.4301
11	Sensor housing	For sensor with process connection: <ul style="list-style-type: none"> <li>≤ DN 50/2": stainless steel 304/1.4301</li> <li>&gt; DN 50/2": stainless steel 316L/1.4435</li> </ul>
12	Sensor measurement tube	Stainless steel 316L/1.4435 with low delta ferrite content
13	Process connection (either clamp connections or flange connections)	Stainless steel 316L/1.4435 with low delta ferrite content
14	Pressure compensating element	Diaphragm in ePTFE, O-ring in silicone 60 Shore A and body in stainless steel (316L/1.4404)

**FLOWave L flowmeter with industrial communication**

**Note:**

The following picture describes a device (Ethernet variant) with 2 × 4-pin M12 circular female connectors, 1 × 5-pin M12 circular male connector and flange process connection.




No.	Element	Material
1	Blind cover or	Stainless steel 304/1.4301
2	Display module	Float glass, stainless steel 304/1.4301
3	Multi-colour LED behind seal (used for e.g. to indicate the status of the product, based on the NAMUR NE 107 standard)	VMQ silicone
4	Transmitter housing	Stainless steel 304/1.4301
5	4-pin M12 circular female connectors with screwed plug	Body in stainless steel 304L/1.4307, contact support in PBT GF30 and seal in EPDM
6	5-pin M12 circular male connector (wired to bus) with screwed plug	Body in stainless steel 316L/1.4404 and seal in NBR
7	Functional earth	Cylinder screw, washer, washer spring: stainless steel A4 blind rivet nut: stainless steel 1.4578/A4
8	Blind cover	VMQ silicone
9	Seal	Stainless steel 304/1.4301
10	Sensor housing	Stainless steel 304/1.4301 <sup>1.)</sup>
11	Sensor measurement tube	Stainless steel 316L/1.4435 with low delta ferrite content
12	Process connection (either clamp connections or flange connections)	Stainless steel 316L/1.4435 with low delta ferrite content
13	Pressure compensating element	Diaphragm: ePTFE; support: polyester; O-ring: silicone 60 Shore A; body: stainless steel (316L/1.4404)

1.) If instead of flange connections there are clamp connections according to DIN 32676 or threaded connections according to DIN 11851, the material of the sensor housing for DN > 50 is stainless steel 316L/1.4435.

### FLOWave S flowmeter

#### Note:

The following picture shows a device with 1 × 5-pin M12 circular male connector and clamp process connection.



No.	Element	Material
1	Cover	Stainless steel 304/1.4301
2	Light guide for status display behind seal (used for e.g. indicating the status of the product, based on the NAMUR NE 107 standard)	PC and O-ring in EPDM
3	Transmitter housing	Stainless steel 304/1.4301
4	5-pin M12 circular male connector (wired to büS) with screwed plug or 8-pin M12 circular male connector (wired to büS as service interface <sup>1.)</sup> and 2 x DO/AO) (with screwed plug)	Stainless steel 316L/1.4404 or 303/1.4305 and seal in EPDM
5	Functional earth	<ul style="list-style-type: none"> <li>Cylinder screw, washer, washer spring: stainless steel A4</li> <li>Jumper of the ground terminal: stainless steel 304L</li> </ul>
6	Seal	VMQ silicone
7	Sensor housing	For sensor with process connection: <ul style="list-style-type: none"> <li>≤ DN 50/2": stainless steel 304/1.4301</li> <li>&gt; DN 50/2": stainless steel 316L/1.4435</li> </ul>
8	Sensor measurement tube	Stainless steel 316L/1.4435 with low delta ferrite content
9	Process connection (either clamp connections or flange connections)	Stainless steel 316L/1.4435 with low delta ferrite content


1.) büS connection only to the Bürkert communicator for configuration and software update of the device. Due to the missing CAN shield the conventional büS/ CANopen communication is not recommended.

## 4. Dimensions

### 4.1. Transmitter of the FLOWave L flowmeter without industrial communication

**Note:**


Dimensions in mm, unless otherwise stated



### 4.2. Transmitter of the FLOWave L flowmeter with industrial communication (Ethernet variant)

**Note:**


Dimensions in mm, unless otherwise stated



### 4.3. Transmitter of the FLOWave S flowmeter

**Note:**


Dimensions in mm, unless otherwise stated



#### 4.4. Flowmeter with clamp process connection

**Note:**

- Dimensions in mm, unless otherwise stated
- Clamp according to DIN 32676 series A, B or C, or SMS 3017



Process connection and pipe size		HL	HS	HL1	HS1	L	L1	øD	øD1	øD2	øD3	øG
[mm]	[inch]											
<b>Clamp according to DIN 32676 series A and process pipe according to DIN 11866 series A (DIN 11850)</b>												
08	–	250	184	220	154	158	105	10	10	14	34	60.3
15 <sup>1.)</sup>	–	250	184	220	154	166	105	16	15.75	19.05	34	60.3
25 <sup>1.)</sup>	–	250	184	220	154	236	105	26	22.1	25.4	50.5	60.3
40 <sup>1.)</sup>	–	250	184	200	134	326	180	38	34.8	38.1	50.5	91
50 <sup>1.)</sup>	–	250	184	200	134	306	180	50	47.5	50.8	64	91
65	–	321	255	251	185	300	210	66	66	70	91	139.7
80	–	321	255	251	185	300	210	81	81	85	106	139.7
<b>Clamp according to DIN 32676 series B and process pipe according to DIN 11866 series B (ISO 1127)</b>												
08	–	250	184	220	154	158	105	10.3	10.3	14	25	60.3
15	–	250	184	220	154	168	105	18.1	18.1	21.3	50.5	60.3
15 <sup>2.)</sup>	–	250	184	220	154	168	105	18.1	18.1	21.3	34	60.3
25	–	250	184	220	154	175	120	29.7	29.7	33.7	50.5	60.3
40	–	250	184	200	134	273	180	44.3	44.3	48.3	64	91
50	–	250	184	200	134	273	180	56.3	56.3	60.3	77.5	91
65	–	321	255	251	185	300	210	72.1	72.1	76.1	91	139.7
80	–	321	255	251	185	300	210	84.3	84.3	88.9	106	139.7
<b>Clamp according to DIN 32676 series C and process pipe according to DIN 11866 series C (ASME BPE)</b>												
–	¾	250	184	220	154	158	105	7.75	7.75	14	25	60.3
–	½	250	184	220	154	158	105	9.4	9.4	14	25	60.3
–	¾	250	184	220	154	143	105	15.75	15.75	19.05	25	60.3
–	1	250	184	220	154	143	105	22.1	22.1	25.4	50.5	60.3
–	1½	250	184	200	134	273	180	34.8	34.8	38.1	50.5	91
–	2	250	184	200	134	273	180	47.5	47.5	50.8	64	91
–	2½	321	255	251	185	300	210	60.2	60.2	63.5	77.5	139.7
–	3	321	255	251	185	300	210	72.9	72.9	76.2	91	139.7
<b>Clamp according to SMS 3017 and process pipe according to SMS 3008</b>												
25 <sup>1.)</sup>	–	250	184	220	154	143	105	22.6	22.1	25.4	50.5	60.3
40 <sup>1.)</sup>	–	250	184	200	134	273	180	35.6	34.8	38.1	50.5	91
50 <sup>1.)</sup>	–	250	184	200	134	273	180	48.6	47.5	50.8	64	91


1.) DIN 32676 series A and SMS 3017 based on ASME BPE pipe dimension with adapted concentric clamp design  
Design according to EHEDG DOC8 guidelines

2.) Similar to DIN 32676 series B but with clamp connection 34.0

### 4.5. Flowmeter with aseptic collar flange (BF)

**Note:**

- Dimensions in mm, unless otherwise stated
- Aseptic collar flange (BF) according to DIN 11864-2 form A series A, B or C




Process connection and pipe size		HL	HS	HL1	HS1	L	L1	L2	øD	øD1	øD2	øD3	øG	øJ	K
[mm]	[inch]														
<b>Flange according to DIN 11864-2 series A and process pipe according to DIN 11866 series A (DIN 11850)</b>															
15 <sup>1.)</sup>	–	250	184	220	154	166	163	105	16	15.75	19.05	59	60.3	9	42
25 <sup>1.)</sup>	–	250	184	220	154	240	237	105	26	22.1	25.4	70	60.3	9	53
40 <sup>1.)</sup>	–	250	184	200	134	330	327	180	38	34.8	38.1	82	91	9	65
50 <sup>1.)</sup>	–	250	184	200	134	310	307	180	50	47.5	50.8	94	91	9	77
65	–	321	255	251	185	300	297	210	66	66	70	113	139.7	9	95
80	–	350	283	265	199	300	297	210	81	81	85	133	168.3	11	112
<b>Flange according to DIN 11864-2 series B and process pipe according to DIN 11866 series B (ISO 1127)</b>															
08	–	250	184	220	154	158	155	105	10.3	10.3	14	54	60.3	9	37
15	–	250	184	220	154	173	170	105	18.1	18.1	21.3	62	60.3	9	45
25	–	250	184	220	154	190	187	120	29.7	29.7	33.7	74	60.3	9	57
40	–	250	184	200	134	278	275	180	44.3	44.3	48.3	88	91	9	71
50	–	250	184	200	134	265	262	180	56.3	56.3	60.3	103	91	9	85
65	–	350	283	265	199	300	29	210	72.1	72.1	76.1	125	168.3	11	104
80	–	350	283	265	199	300	197	210	84.3	84.3	88.9	137	168.3	11	116
<b>Flange according to DIN 11864-2 series C and process pipe according to DIN 11866 series C (ASME BPE)</b>															
–	½	250	184	220	154	158	155	105	9.4	9.4	14	54	60.3	9	37
–	¾	250	184	220	154	171	168	105	15.75	15.75	19.05	59	60.3	9	42
–	1	250	184	220	154	168	165	105	22.1	22.1	25.4	66	60.3	9	49
–	1½	250	184	200	134	278	275	180	34.8	34.8	38.1	79	91	9	62
–	2	250	184	200	134	278	275	180	47.5	47.5	50.8	92	91	9	75

1.) DIN 11864-2 series A based on ASME BPE pipe dimension with adapted concentric flange design  
Design according to EHEDG DOC8 guidelines

### 4.6. Flowmeter with aseptic collar clamp (BKS)

**Note:**

- Dimensions in mm, unless otherwise stated
- Aseptic collar clamp (BKS) according to DIN 11864-3 form A series A, B or C



Process connection and pipe size		HL1	HS1	L	L1	L2	ø D	ø D1	ø D2	ø D3	ø G
[mm]	[inch]										
<b>Clamp according to DIN 11864-3 series A and process pipe according to DIN 11866 series A (DIN 11850)</b>											
15 <sup>1.)</sup>	-	220	154	166	163	105	16	15.75	19.05	34	60.3
25 <sup>1.)</sup>	-	220	154	240	237	105	26	22.1	25.4	50.5	60.3
40 <sup>1.)</sup>	-	200	134	330	327	180	38	34.8	38.1	64	91
50 <sup>1.)</sup>	-	200	134	310	307	180	50	47.5	50.8	77.5	91
<b>Clamp according to DIN 11864-3 series B and process pipe according to DIN 11866 series B (ISO 1127)</b>											
08	-	220	154	158	155	105	10.3	10.3	14	34	60.3
15	-	220	154	169	166	105	18.1	18.1	21.3	34	60.3
25	-	220	154	190	187	120	29.7	29.7	33.7	50.5	60.3
40	-	200	134	280	277	180	44.3	44.3	48.3	64	91
50	-	200	134	271	268	180	56.3	56.3	60.3	91	91
<b>Clamp according to DIN 11864-3 series C and process pipe according to DIN 11866 series C (ASME BPE)</b>											
-	1/2	220	154	158	155	105	9.4	9.4	14	34	60.3
-	3/4	220	154	167	164	105	15.75	15.75	19.05	34	60.3
-	1	220	154	164	161	105	22.1	22.1	25.4	50.5	60.3
-	1 1/2	200	134	278	275	180	34.8	34.8	38.1	64	91
-	2	200	134	279	276	180	47.5	47.5	50.8	77.5	91


1.) DIN 11864-3 series A based on ASME BPE pipe dimension with adapted concentric clamp design  
Design according to EHEDG DOC8 guidelines



### 4.7. Flowmeter with thread connection

**Note:**

- Dimensions in mm, unless otherwise stated
- Thread connection according to DIN 11851 series A




Process connection and pipe size [mm]	HL	HS	HL1	HS1	L	L1	L2	ø D	ø D2	ø D3 <sup>1.)</sup>	ø G
<b>Thread according to DIN 11851</b>											
65	321	255	251	185	300	284	210	66	70	Rd 95 x 1/6	139.7
80	321	255	251	185	300	284	210	81	85	Rd 110 x 1/4	139.7

1.) Thread according to DIN 405-1

## 5. Performance specifications

### 5.1. Medium temperature diagram



DTS 1000270652 EN Version: U Status: RL (released | freigegeben | valide) printed: 12.07.2023

## 5.2. Measurement deviation table

### Note:

- This table shows the measurement deviations according to the pipe connection standards per measuring range.
- In the following table, the term “full scale” refers to full scale of volume flow rate, i.e. the flow rate corresponding to 10 m/s flow velocity.

DN	Pipe standard	Flow velocity in sensor tube in [m/s] in % of full scale	0.1 1	1 10	10 100
3/8"	ASME BPE	Volume flow rate range [m <sup>3</sup> /h]	0.017 ± 0.08 % of full scale	0.17 ± 0.4 % of measured value	1.7
1/2"	ASME BPE	Volume flow rate range [m <sup>3</sup> /h]	0.025 ± 0.08 % of full scale	0.25 ± 0.4 % of measured value	2.5
08	ISO 1127 DIN 11850	Volume flow rate range [m <sup>3</sup> /h]	0.03 ± 0.08 % of full scale	0.30 ± 0.4 % of measured value	3
3/4" 15	ASME BPE DIN 11850	Volume flow rate range [m <sup>3</sup> /h]	0.07 ± 0.08 % of full scale	0.7 ± 0.4 % of measured value	7
15	ISO 1127	Volume flow rate range [m <sup>3</sup> /h]	0.10 ± 0.08 % of full scale	1.0 ± 0.4 % of measured value	10
1" 25 25	ASME BPE DIN 11850 SMS 3008	Volume flow rate range [m <sup>3</sup> /h]	0.14 ± 0.08 % of full scale	1.4 ± 0.4 % of measured value	14
25	ISO 1127	Volume flow rate range [m <sup>3</sup> /h]	0.25 ± 0.08 % of full scale	2.5 ± 0.4 % of measured value	25
1 1/2" 40 40	ASME BPE DIN 11850 SMS 3008	Volume flow rate range [m <sup>3</sup> /h]	0.35 ± 0.08 % of full scale	3.5 ± 0.4 % of measured value	35
40	ISO 1127	Volume flow rate range [m <sup>3</sup> /h]	0.56 ± 0.08 % of full scale	5.6 ± 0.4 % of measured value	56
2" 50 50	ASME BPE DIN 11850 SMS 3008	Volume flow rate range [m <sup>3</sup> /h]	0.64 ± 0.08 % of full scale	6.4 ± 0.4 % of measured value	64
50	ISO 1127	Volume flow rate range [m <sup>3</sup> /h]	0.90 ± 0.08 % of full scale	9.0 ± 0.4 % of measured value	90
2 1/2"	ASME BPE	Volume flow rate range [m <sup>3</sup> /h]	1.02 ± 0.08 % of full scale	10.2 ± 0.4 % of measured value	102
65	DIN 11850	Volume flow rate range [m <sup>3</sup> /h]	1.23 ± 0.08 % of full scale	12.3 ± 0.4 % of measured value	123
65	ISO 1127	Volume flow rate range [m <sup>3</sup> /h]	1.47 ± 0.08 % of full scale	14.7 ± 0.4 % of measured value	147
3"	ASME BPE	Volume flow rate range [m <sup>3</sup> /h]	1.50 ± 0.08 % of full scale	15.0 ± 0.4 % of measured value	150
80	DIN 11850	Volume flow rate range [m <sup>3</sup> /h]	1.85 ± 0.08 % of full scale	18.5 ± 0.4 % of measured value	185
80	ISO 1127	Volume flow rate range [m <sup>3</sup> /h]	2.00 ± 0.08 % of full scale	20.0 ± 0.4 % of measured value	200

## 5.3. Refresh time table

Selectable mode	Volume flow rate	Density	Mass flow rate
Very short	~ 25 ms	1 s	~ 25 ms
Short	~ 40 ms	1 s	~ 40 ms
Long	~ 75 ms	0.5 s	~ 75 ms

## 6. Product installation

### 6.1. Installation notes

**Note:**

The device is not suitable for use in gaseous media and steam. However, their flow does not have any negative effect on the device or its operation. Other liquids flowing through again afterwards are measured correctly as before.

The factory calibration of the FLOWave is done under reference conditions with inlet (40xDN) and outlet (1 xDN) distances and the appropriate internal diameter of the pipes.

Deviation from reference conditions can be easily adjusted through the use of a built-in K factor adjustment or Teach in procedure.

We can support you if necessary, please do not hesitate to contact us.

The device can be installed into either horizontal, oblique or vertical pipes. But an installation on a vertical pipe will be better to prevent air or gas bubbles inside the measurement area. **For proper operation always ensure a totally filled measurement tube.**

Conformity to 3A and EHEDG requires an angle of at least 5° (for SMS or series A connections) or 3° (all others available connections) against horizontal to ensure complete draining however this not necessary for proper operation of the FLOWave.

The suitable pipe size can be selected using the diagram for selecting the nominal diameter of the pipe. See chapter "6.2. Selection of the nominal diameter" on page 27.

### 6.2. Selection of the nominal diameter

The following graph is used to determine the appropriate DN of the pipe and fitting for the application, according to the fluid velocity and the flow rate. On the chart, the intersection of flow velocity and flow rate gives the appropriate diameter.

**Example 1:**


Flowmeter with process connection according to DIN 32676 series B (pipe ISO 1127) or DIN 11864-2 form A series B (pipe ISO 1127)

- Nominal flow: 10 m³/h
  - Optimal flow rate: 1...3 m/s
- Result: Select a pipe size of DN 40 or DN 50

**Example 2:**

Flowmeter with process connection according to DIN 32676 series A (pipe DIN 11850) or DIN 11864-2 series A (pipe DIN 11850)


- Nominal flow: 10 m³/h
  - Optimal flow rate: 1...3 m/s
- Result: Select a pipe size of DN 40 or DN 50



### 6.3. Mounting options


#### FLOWave L flowmeter

The product is delivered as described in position 1 in the picture below. The position of the transmitter can be changed in 90° steps. The position of the display module and the blind cover can also be changed in steps of 90° both on the top of the unit and on the front face.



Position 1

For safety reasons the display module and blind cover on the top or front are locked. The display module and blind cover can be unlocked with a magnetic key which is included in the delivery of each device.



#### FLOWave S flowmeter

The product is delivered as described in position 1 in the picture below. The position of the transmitter can be changed in 90° steps. For safety reasons the transmitter is locked. The transmitter can be unlocked with a magnetic key which is included in the delivery of each device.



Position 1

## 7. Product operation


### 7.1. Measuring principle

The technology used is based on SAW (Surface Acoustic Waves). The type of wave propagation is similar to what happens when an earthquake occurs in nature.

In the case of FLOWave it is a miniaturized signal, not running on the surface of the earth but on a measurement tube. FLOWave uses so called interdigital transducers which are placed on flattened areas of the tube surface. Each one acts as emitter as well as receiver. Two of them (nos. 1 and 4) emit forward, in the direction of the liquid flow, the others (nos. 2 and 3) backwards, i.e. in the opposite direction to the direction of flow. The propagation time is measured from emitter to receiver. The difference between the forward and backward propagation time of the waves is proportional to the volume flow rate.

The high performance measurement is achieved by the following aspects:

- Each emitter sends multiple signals that are received on two other receivers
- The results are based on the reception of the signals that pass through the liquid one or more times.
- Several measurements can be performed based on the collected information. Many properties of the liquid can be derived, including the flow velocity, the fluid density, the fraction of the transmitted signal (“acoustic transmission factor”), and the so-called “differentiation factor” (see following), as well as information about the presence of gas bubbles or solid parts.
- Mass flow is calculated from fluid density and volume flow.
- Mass flow and density measurements are an option on standard FLOWave flowmeters, which requires adjustment and calibration during manufacture. It is therefore necessary to specify whether or not the device is to be equipped with these features when ordering the device.



This figure shows, as an example, the reception signals when interdigital transducer 1 is transmitting. The emitter excitation produces the SAW with a frequency of more than 1 MHz.

As a result of the emission of these waves, the following effects occur:

- A wave propagates along the surface of the tube (see orange line).
- A wave is emitted (see green line) and passes through the liquid towards the opposite side of the tube at a certain angle, which depends mainly on the speed of propagation on the surface of the tube and in the liquid.
- Upon reaching the opposite side of the tube, two effects take place.
  - A wave is triggered in the tube and propagates (see green line) to receiver 3
  - A wave is triggered in the liquid (see yellow line) and passes through it again to the opposite wall of the tube. The analysis of the transmitted and received waves allows deriving the process values (velocity, density, flow rates).

These effects are repeated and thus generate the many signals received, which are differentiated in the image with different colours.

## 7.2. Special functions

**Note:**

DF, ATF, density and mass flow features must be selected upon initial order of device.

For the detection of gas bubbles and solid particles the device (from firmware version 01.05.00) includes a so called “acoustic transmission factor (ATF)” with a measurement range of 5...120 %, whose value is constantly recorded and directly influenced by the presence of gas bubbles and solid particles.

A “differentiation factor (DF)”, with a measuring range of 0.8...1.3, is available for the detection and differentiation of liquids. This continuously measured value, which uses water as a reference fluid, is temperature-compensated and so its value is representative in a tight value range for each liquid. The changes in value of this process measurement enable differentiation between different liquids.

Before SW version 05.00.00, the differentiation factor was named density factor. As the density option has been added, the name has been changed to avoid confusion.

## 8. Product design and assembly


### 8.1. Product assembly

The 8098 flowmeter consists of a S097 flow sensor and a FLOWave L transmitter (variant FLOWave L flowmeter) or FLOWave S transmitter (variant FLOWave S flowmeter).

The flow sensor includes the measurement tube equipped with interdigital transducers, the sensor housing and the process connections in accordance to the standards ISO, ASME BPE, DIN, SMS. At present the sensor size ranges from DN 08 to DN 80 or from 3/8" to 3".

The FLOWave L flowmeter is available with or without display. The high resolution display includes a capacitive working keypad for all interactive user actions, guided by a user friendly menu system. The output signals include one analogue output and one digital output; while a third output signal can be switched between analogue and digital through parametrisation. Electrical connection is done on push-in connectors via two cable glands and/or one M12 circular connector.

The FLOWave S flowmeter is only available without display. The electrical connection is made via an M12 circular male connector.



DTS 1000270652 EN Version: U Status: RL (released | freigegeben | valide) printed: 12.07.2023

## 9. Product accessories

**Note:**


To set up a device without a display, please use the USB-büS interface, Type 8923, the Bürkert Communicator Type 8920. For the FLOWave S with two outputs, the büS adaptor cable article no. 773286 is required too.

See **Software manual Type 8920** ▶ for more information.

Accessories	No.	Description
	1	Quick-Start
	2	Power supply: 100...240 V AC/ 24 V DC 1 A and adaptors for power supply worldwide use
	3	büS terminating resistor on büS Y-splitter
	4	5-pin M12 circular male connector wired on free end cable
	5	büS connection cable with 5-pin M12 circular male connector, micro USB B plug
	6	büS adapter with 5-pin M12 circular male connector, A-coded to 5-pin M12 circular male connector, A-coded
	7	büS stick (USB to büS/CANopen adaptor)
	8	büS service cable with 5-pin M12 circular female connector, mini USB and circular plug-in connectors for power supply
	9	Magnetic key
	10	CD - Communicator (30-day license without registration, update and licensing over Bürkert home page)

## 10. Ordering information

### 10.1. Bürkert eShop



**Bürkert eShop – Easy ordering and quick delivery**

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.


[Order online now](#)

### 10.2. Recommendation regarding product selection

**Note:**

- The installation of the flowmeter in a pipe requires the use of counter-connection, seals, fixing elements, etc. depending on the used norm.
- The drawings show the installation with a FLOWave L variant of the flow meter. The installation is also valid for the FLOWave S variant.

For instance with middle-sized devices:

Connection	Description
	<p><b>With clamp according to DIN 32676 series A</b></p> <p>To insert a FLOWave DN 40 with clamps according to DIN 32676 series A (with Ra &lt; 0.8 µm) to a pipe according to DIN 11866 series A (DIN 11850), the <b>correct adapters to be selected and separately ordered</b> are for instance</p> <ul style="list-style-type: none"> <li>• 2 x <b>BBS-25</b> clamp ferrules, article no. 747237, see <b>data sheet Type BBS-25</b> ▶ for more information</li> <li>• 2 x the appropriate seals (not provided)</li> <li>• 2 x the corresponding clamps, article no. 731164</li> </ul>



Connection	Description
	<p><b>With aseptic collar flange (BF) according to DIN 11864-2 form A</b></p> <p>To insert a FLOWave DN 40 with collar flanges according to DIN 11864-2 series B (with Ra &lt;math&gt;&lt; 0.8 \mu\text{m}&lt;/math&gt;) to a pipe according to DIN 11866 series B (ISO 1127), the <b>correct adapters to be selected and separately ordered</b> are for instance</p> <ul style="list-style-type: none"> <li>• 2x <b>BBS-06</b> aseptic groove flange, article no. 731860, see <b>data sheet Type BBS-06</b> ▶ for more information</li> <li>• 2x the appropriate seals (not provided)</li> <li>• 8x the corresponding screws, flat washers and nuts (please refer to the DIN 11864-2 standard)</li> </ul>
	<p><b>With aseptic collar clamp (BKS) according to DIN 11864-3 form A</b></p> <p>To insert a FLOWave 1" with hygienic collar clamps according to DIN 11864-3 series C (with Ra &lt;math&gt;&lt; 0.8 \mu\text{m}&lt;/math&gt;) to a pipe according to DIN 11866 series C (ASME BPE), the <b>correct adapters to be selected and separately ordered</b> are for instance</p> <ul style="list-style-type: none"> <li>• 2x <b>BBS-05</b> aseptic groove clamp, article no. 730272, see <b>data sheet Type BBS-05</b> ▶ for more information</li> <li>• 2x the appropriate seals (not provided)</li> <li>• 2x the corresponding clamps, article no. 731164</li> </ul>
	<p><b>With thread according to DIN 11851</b></p> <p>To insert a FLOWave with thread according to DIN 11851 series A to a pipe according to DIN 11850, suitable adapters (not available from Bürkert) are required, for instance</p> <ul style="list-style-type: none"> <li>• 2x the conical ferrule</li> <li>• 2x the appropriate DIN 11851 seal</li> <li>• 2x the corresponding round slotted nut</li> </ul>

### 10.3. Bürkert product filter



#### Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

### 10.4. Bürkert 3D Model

#### Applications & Tools



#### Bürkert 3D Model - Interactive Animation

3D Model and Interactive Animation are available on the website of the flowmeter Type 8098.

See **website of the Type 8098** ▶ under “Applications and Tools”.















### 10.5. Ordering chart FLOWave L flowmeter with or without industrial communication

Clamp process connection acc. to DIN 32676 series A for pipe acc. to DIN 11866 series A (DIN 11850)

**Note:**

- To set up a device without a display, please use the USB-büS interface, Type 8923 (has to be ordered separately - see chapter "9. Product accessories" on page 31 and "10.7. Ordering chart accessories" on page 41).
- The following variants are equipped with a display and the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diameter <sup>1.)</sup> [mm]	Maximal flow rate [m <sup>3</sup> /h]	Dimensions <sup>2.)</sup> D2 x s; D3 [mm]	Surface quality		Certifications		Article no.
			Housing, outer surface of measurement tube [µm]	Inner surface of measurement tube [µm]	3A (28-06)	EHEDG <sup>3.)</sup>	
<b>Variant without industrial communication (2 cable glands<sup>4.)</sup> M20 x1.5 + 1 x 5-pin M12 circular male connector), operating voltage of 12...35 V DC</b>							
15	7	19.05 x 1.65; 34.0	Ra < 1.6	Ra < 0.8	Yes	Yes	569159 
				Ra < 0.4			569161 
25	14	25.4 x 1.65; 50.5		Ra < 0.8			569163 
				Ra < 0.4			569165 
40	35	38.1 x 1.65; 50.5		Ra < 0.8			569167 
				Ra < 0.4			569169 
50	64	50.8 x 1.65; 64.0		Ra < 0.8			569171 
				Ra < 0.4			569173 
65	123	70.0 x 2.0; 91.0		Ra < 0.8			573445 
				Ra < 0.4			573373 
80	185	85.0 x 2.0; 106.0		Ra < 0.8			573446 
				Ra < 0.4			573374 

1.) = Process connection and pipe size

















2.) D2 for holder, s = thickness and D3 for clamp

3.) The EHEDG compliance is only if used in combination with gaskets from Combifit International B.V.

4.) Cable gland in nickel plated brass valid

**Clamp process connection acc. to DIN 32676 series B for pipe acc. to DIN 11866 series B (ISO 1127)**
**Note:**

- To set up a device without a display, please use the USB-büS interface, Type 8923 (has to be ordered separately - see chapter “9. Product accessories” on page 31 and “10.7. Ordering chart accessories” on page 41).
- The following variants are equipped with a display and the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diameter <sup>1.)</sup> [mm]	Maximal flow rate [m <sup>3</sup> /h]	Dimensions <sup>2.)</sup> D2 x s; D3 [mm]	Surface quality		Certifications		Article no.
			Housing, outer surface of measurement tube [µm]	Inner surface of measurement tube [µm]	3A (28-06)	EHEDG <sup>3.)</sup>	
<b>Variant without industrial communication (2 cable glands<sup>4.)</sup> M20x1.5 + 1 x 5-pin M12 circular male connector), operating voltage of 12...35 V DC</b>							
08	3	14 x 1.85; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	573126 
				Ra < 0.4			573128 
15	10	21.3 x 1.6; 50.5 21.3 x 1.6; 34.0 21.3 x 1.6; 50.5 21.3 x 1.6; 34.0	Ra < 1.6	Ra < 0.8	Yes	Yes	566187 
				Ra < 0.4		No	566235 
				Ra < 0.8		Yes	566195 
				Ra < 0.4		No	566237 
25	25	33.7 x 2.0; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	566188 
				Ra < 0.4		566196 	
40	56	48.3 x 2.0; 64.0	Ra < 1.6	Ra < 0.8	Yes	Yes	566189 
				Ra < 0.4		566197 	
50	90	60.3 x 2.0; 77.5	Ra < 1.6	Ra < 0.8	Yes	Yes	566190 
				Ra < 0.4		566198 	
65	147	76.1 x 2.0; 91.0	Ra < 1.6	Ra < 0.8	Yes	Yes	573442 
				Ra < 0.4		573370 	
80	200	88.9 x 2.3; 106.0	Ra < 1.6	Ra < 0.8	Yes	Yes	573443 
				Ra < 0.4		573371 	

1.) = Process connection and pipe size

2.) D2 for holder; s = thickness; D3: clamp

















3.) The EHEDG compliance is only valid if used in combination with gaskets from Combifit International B.V.

4.) Cable gland in nickel plated brass

Clamp process connection acc. to DIN 32676 series C for pipe acc. to DIN 11866 series C (ASME BPE)

**Note:**

- To set up a device without a display, please use the USB-büS interface, Type 8923 (has to be ordered separately - see chapter “9. Product accessories” on page 31 and “10.7. Ordering chart accessories” on page 41).
- The following variants are equipped with a display and the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diame- ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications			Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube	3A (28-06)	EHEDG <sup>3.)</sup>	UL	
[inch]	[m <sup>3</sup> /h]	[mm]	[µm]	[µm]				
<b>Variant without industrial communication (2 cable glands<sup>4.)</sup> M20 x 1.5 + 1 x 5-pin M12 circular male connector), operating voltage of 12...35 V DC</b>								
3/8	1.7	14.00 x 3.125; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573112 
				Ra < 0.4			Yes	573114 
1/2	2.5	14.00 x 2.3; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573119 
				Ra < 0.4			Yes	573123 
3/4	7	19.05 x 1.65; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	566203 
				Ra < 0.4			Yes	569675 
1	14	25.4 x 1.65; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	566204 
				Ra < 0.4			Yes	569676 
1 1/2	35	38.1 x 1.65; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	566205 
				Ra < 0.4			Yes	569677 
2	64	50.8 x 1.65; 64.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	566206 
				Ra < 0.4			Yes	569678 
2 1/2	100	63.5 x 1.65; 77.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573448 
				Ra < 0.4			Yes	574710 
3	150	76.2 x 1.65; 91.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573449 
				Ra < 0.4			Yes	574711 

Diame- ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications			Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube	3A (28-06)	EHEDG <sup>3.)</sup>	UL	
[inch]	[m <sup>3</sup> /h]	[mm]	[µm]	[µm]				
<b>Variant with industrial communication (Ethernet variant, 2 x 4-pin M12 circular female connectors + 1 x 5-pin M12 circular male connector), operating voltage of 12...35 V DC</b>								
3/8	1.7	14.00 x 3.125; 25.0	Ra < 1.6	Ra < 0.4	Yes	Yes	No	573117
							Yes	573118
1/2	2.5	14.00 x 2.3; 25.0					No	573124
							Yes	573125
3/4	7	19.05 x 1.65; 25.0					No	570444
							Yes	569679
1	14	25.4 x 1.65; 50.5					No	570445
							Yes	569680
1 1/2	35	38.1 x 1.65; 50.5					No	570446
							Yes	569681
2	64	50.8 x 1.65; 64.0	No	570447				
			Yes	569682				
2 1/2	100	63.5 x 1.65; 77.5	No	574716				
			Yes	574720				
3	150	76.2 x 1.65; 91.0	No	574717				
			Yes	574721				

1.) = Process connection and pipe size

2.) D2 for holder; s = thickness; D3: clamp

3.) The EHEDG compliance is only valid if used in combination with gaskets from Combifit International B.V.

4.) Cable gland in nickel plated brass

#### Thread process connection acc. to DIN 11851 series A for pipe acc. to DIN 11866 series A (DIN 11850)

##### Note:

- To set up a device without a display, please use the USB-büS interface, Type 8923 (has to be ordered separately - see chapter "9. Product accessories" on page 31 and "10.7. Ordering chart accessories" on page 41).
- The following variants are equipped with a display and the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diame- ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications		Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube	3A (28-06)	EHEDG <sup>2.)</sup>	
[mm]	[m <sup>3</sup> /h]	[mm]	[µm]	[µm]			
<b>Variant without industrial communication (2 cable glands<sup>4.)</sup> M20 x 1.5 + 1 x 5-pin M12 circular male connector), operating voltage of 12...35 V DC</b>							
65	123	70.0 x 2.0; Rd 95 x 1/6	Ra < 1.6	Ra < 0.8	Yes	Yes	573463
80	185	85.0 x 2.0; Rd 110 x 1/4		Ra < 0.8			573464

1.) = Process connection and pipe size






2.) D2 for holder; s = thickness; D3: thread connection

3.) The EHEDG compliance is only valid if used in combination with EHEDG-compliant gaskets from

1. Kieselmann GmbH, Germany (ASEPTO-STAR k-flex upgrade gaskets) or

2. Siersema Componenten Service (S.K.S.) B.V. (Netherlands SKS gasket set DIN 11851 EHEDG with EPDM or FKM inner gasket)

4.) Cable gland in nickel plated brass

Further versions on request	
 <p><b>Process connection</b></p> <ul style="list-style-type: none"> <li>For pipe DIN 11850:                             <ul style="list-style-type: none"> <li>Clamp DIN 11864-3</li> <li>Flange DIN 11864-2</li> </ul> </li> <li>For pipe ISO 1127:                             <ul style="list-style-type: none"> <li>Clamp DIN 11864-3</li> <li>Flange DIN 11864-2</li> </ul> </li> <li>For pipe ASME BPE:                             <ul style="list-style-type: none"> <li>Clamp DIN 11864-3</li> <li>Flange DIN 11864-2</li> </ul> </li> <li>For pipe SMS 3008: SMS 3017</li> </ul>	<div style="display: flex; align-items: center;">  <div> <p><b>Additional</b></p> <ul style="list-style-type: none"> <li>With/without display</li> <li>Without differentiation factor (DF)</li> <li>Without acoustic transmission factor (ATF)</li> <li>With density and mass flow</li> <li>Ethernet module (EtherNet/IP, PROFINET, Modbus TCP/IP, ETHERCAT)</li> <li>ATEX/IECEX</li> </ul> </div> </div> <div style="display: flex; align-items: center; margin-top: 10px;">  <div> <p><b>Material</b></p> <ul style="list-style-type: none"> <li>With inner surface of measurement tube                             <ul style="list-style-type: none"> <li>Ra &lt; 0.8 µm (30 µin.)</li> <li>Ra &lt; 0.4 µm (15 µin.) (electro-polished) according to ISO 4288</li> </ul> </li> </ul> </div> </div>
 <p><b>Orifice</b></p> <ul style="list-style-type: none"> <li>08...80 mm</li> <li>3/8...3 inch</li> </ul>	 <p><b>Electrical connection</b></p> <p>Cable gland in stainless steel</p>





For any other variants, please use the product enquiry form at the end of this data sheet or check the readily available article no. listed in the Bürkert eShop.

### 10.6. Ordering chart FLOWave S flowmeter

Clamp process connection acc. to DIN 32676 series A for pipe acc. to DIN 11866 series A (DIN 11850)

**Note:**

The following variants are equipped with the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diame-ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications		Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube	3A (28-06)	EHEDG <sup>3.)</sup>	
[mm]	[m³/h]	[mm]	[µm]	[µm]			
<b>Electrical connection: 1 x 8-pin M12 circular male connector, operating voltage of 12...35 V DC</b>							
65	123	70.0x2.0; 91.0	Ra < 1.6	Ra < 0.8	Yes	Yes	574689 
				Ra < 0.4			573421 
80	185	85.0x2.0; 106.0		Ra < 0.8			574690 
				Ra < 0.4			573422 

1.) = Process connection and pipe size





























2.) D2 for holder; s = thickness; D3: clamp

3.) The EHEDG compliance is only valid if used in combination with gaskets from Combit International B.V.

DTS 1000270652 EN Version: U Status: RL (released | freigegeben | valide) printed: 12.07.2023

**Clamp process connection acc. to DIN 32676 series B for pipe acc. to DIN 11866 series B (ISO 1127)**
**Note:**

The following variants are equipped with the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diame- ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications		Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube	3A (28-06)	EHEDG <sup>3.)</sup>	
[mm]	[m <sup>3</sup> /h]	[mm]	[µm]	[µm]			
<b>Electrical connection: 1 x 5-pin M12 circular male connector, operating voltage of 12...35 V DC</b>							
08	3	14 x 1.85; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	573716 
				Ra < 0.4			573717 
15	10	21.3 x 1.6; 50.5 21.3 x 1.6; 34.0 21.3 x 1.6; 50.5 21.3 x 1.6; 34.0	Ra < 1.6	Ra < 0.8	Yes	Yes	573093 
				Ra < 0.4			573094 
				Ra < 0.4			573098 
				Ra < 0.4			573099 
25	25	33.7 x 2.0; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	573095 
				Ra < 0.4			573100 
40	56	48.3 x 2.0; 64.0	Ra < 1.6	Ra < 0.8	Yes	Yes	573096 
				Ra < 0.4			573101 
50	90	60.3 x 2.0; 77.5	Ra < 1.6	Ra < 0.8	Yes	Yes	573097 
				Ra < 0.4			573102 
<b>Electrical connection: 1 x 8-pin M12 circular male connector, operating voltage of 12...35 V DC</b>							
08	3	14 x 1.85; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	571780 
				Ra < 0.4			571781 
15	10	21.3 x 1.6; 50.5 21.3 x 1.6; 34.0 21.3 x 1.6; 50.5 21.3 x 1.6; 34.0	Ra < 1.6	Ra < 0.8	Yes	Yes	571782 
				Ra < 0.4			571783 
				Ra < 0.4			571784 
				Ra < 0.4			571785 
25	25	33.7 x 2.0; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	571786 
				Ra < 0.4			571787 
40	56	48.3 x 2.0; 64.0	Ra < 1.6	Ra < 0.8	Yes	Yes	571788 
				Ra < 0.4			571789 
50	90	60.3 x 2.0; 77.5	Ra < 1.6	Ra < 0.8	Yes	Yes	571790 
				Ra < 0.4			571791 
65	147	76.1 x 2.0; 91.0	Ra < 1.6	Ra < 0.8	Yes	Yes	574686 
				Ra < 0.4			573418 
80	200	88.9 x 2.3; 106.0	Ra < 1.6	Ra < 0.8	Yes	Yes	574687 
				Ra < 0.4			573419 

1.) = Process connection and pipe size

2.) D2 for holder; s = thickness; D3: clamp

3.) The EHEDG compliance is only valid if used in combination with gaskets from Combifit International B.V.

Clamp process connection acc. to DIN 32676 series C for pipe acc. to DIN 11866 series C (ASME BPE)

Note:

The following variants are equipped with the special functions ATF (acoustic transmission factor) and DF (differentiation factor).

Diame-ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications			Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube	3A (28-06)	EHEDG <sup>3.)</sup>	UL	
[inch]	[m <sup>3</sup> /h]	[mm]	[µm]	[µm]				
<b>Electrical connection: 1 x 5-pin M12 circular male connector, operating voltage of 12...35 V DC</b>								
3/8	1.7	14.00 x 3.125; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573710
				Ra < 0.4			Yes	573711
1/2	2.5	14.00 x 2.3; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573712
				Ra < 0.4			Yes	573713
3/4	7	19.05 x 1.65; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573714
				Ra < 0.4			Yes	573715
1	14	25.4 x 1.65; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573085
				Ra < 0.4			Yes	573086
1 1/2	35	38.1 x 1.65; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573087
				Ra < 0.4			Yes	573088
2	64	50.8 x 1.65; 64.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573089
				Ra < 0.4			Yes	573090
2 1/2	100	63.5 x 1.65; 77.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573091
				Ra < 0.4			Yes	573092
3	150	76.2 x 1.65; 91.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573093
				Ra < 0.4			Yes	573094
<b>Electrical connection: 1 x 8-pin M12 circular male connector, operating voltage of 12...35 V DC</b>								
3/8	1.7	14.00 x 3.125; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571792
				Ra < 0.4			Yes	571793
1/2	2.5	14.00 x 2.3; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571794
				Ra < 0.4			Yes	571795
3/4	7	19.05 x 1.65; 25.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571796
				Ra < 0.4			Yes	571797
1	14	25.4 x 1.65; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571798
				Ra < 0.4			Yes	571799
1 1/2	35	38.1 x 1.65; 50.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571800
				Ra < 0.4			Yes	571801
2	64	50.8 x 1.65; 64.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571802
				Ra < 0.4			Yes	571803
2 1/2	100	63.5 x 1.65; 77.5	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571804
				Ra < 0.4			Yes	571805
3	150	76.2 x 1.65; 91.0	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571806
				Ra < 0.4			Yes	571807
3 1/2	300	91.4 x 1.65; 114.3	Ra < 1.6	Ra < 0.8	Yes	Yes	No	571808
				Ra < 0.4			Yes	571809
4	450	114.3 x 1.65; 141.3	Ra < 1.6	Ra < 0.8	Yes	Yes	No	574692
				Ra < 0.4			Yes	574693
4 1/2	600	141.3 x 1.65; 171.3	Ra < 1.6	Ra < 0.8	Yes	Yes	No	573424
				Ra < 0.4			Yes	574718
5	750	171.3 x 1.65; 201.3	Ra < 1.6	Ra < 0.8	Yes	Yes	No	574693
				Ra < 0.4			Yes	573425
5 1/2	900	201.3 x 1.65; 231.3	Ra < 1.6	Ra < 0.8	Yes	Yes	No	574719
				Ra < 0.4			Yes	574720

1.) = Process connection and pipe size

2.) D2 for holder; s = thickness; D3: clamp

3.) The EHEDG compliance is only valid if used in combination with gaskets from Combifit International B.V.

DTS 1000270652 EN Version: U Status: RL (released | freigegeben | valide) printed: 12.07.2023

Thread process connection acc. to DIN 11851 series A for pipe acc. to DIN 11866 series A (DIN 11850)

**Note:**

The following variants are equipped with the special functions ATF (acoustic transmission factor) and DF (density factor).

Diame- ter <sup>1.)</sup>	Maximal flow rate	Dimensions <sup>2.)</sup> D2 x s; D3	Surface quality		Certifications		Article no.
			Housing, outer surface of measurement tube	Inner surface of measurement tube			
[mm]	[m <sup>3</sup> /h]	[mm]	[µm]	[µm]	3A (28-06)	EHEDG <sup>3.)</sup>	
<b>Electrical connection: 1 x 8-pin M12 circular male connector, operating voltage of 12...35 V DC</b>							
65	123	70.0x2.0; Rd 95 x 1/6	Ra < 1.6	Ra < 0.8	Yes	Yes	574707
80	185	85.0x2.0; Rd 110 x 1/4		Ra < 0.8			574708

1.) = Process connection and pipe size

2.) D2 for holder; s = thickness; D3: thread connection

3.) The EHEDG compliance is only valid if used in combination with EHEDG-compliant gaskets from

1. Kieselmann GmbH, Germany (ASEPTO-STAR k-flex upgrade gaskets) or

2. Siersema Componenten Service (S.K.S.) B.V. (Netherlands SKS gasket set DIN 11851 EHEDG with EPDM or FKM inner gasket)









































### Further versions on request

<p><b>Process connection</b></p> <ul style="list-style-type: none"> <li>For pipe DIN 11850:           <ul style="list-style-type: none"> <li>Clamp DIN 32676</li> <li>Clamp DIN 11864-3</li> <li>Flange DIN 11864-2</li> </ul> </li> <li>For pipe ISO 1127:           <ul style="list-style-type: none"> <li>Clamp DIN 11864-3</li> <li>Flange DIN 11864-2</li> </ul> </li> <li>For pipe ASME BPE:           <ul style="list-style-type: none"> <li>Clamp DIN 11864-3</li> <li>Flange DIN 11864-2</li> </ul> </li> <li>For pipe SMS 3008: SMS 3017</li> </ul>	<p><b>Orifice</b></p> <ul style="list-style-type: none"> <li>08...80 mm</li> <li>3/8...3 inch</li> </ul>
	<p><b>Additional</b></p> <ul style="list-style-type: none"> <li>Without differentiation factor (DF)</li> <li>Without acoustic transmission factor (ATF)</li> <li>With density and mass flow</li> <li>ATEX/IECEX</li> </ul>
	<p><b>Material</b></p> <ul style="list-style-type: none"> <li>With inner surface of measurement tube           <ul style="list-style-type: none"> <li>Ra &lt; 0.8 µm (30 µin.)</li> <li>Ra &lt; 0.4 µm (15 µin.) (electro-polished) according to ISO 4288</li> </ul> </li> </ul>
	<p><b>Electrical connection</b></p> <ul style="list-style-type: none"> <li>1 x 5-pin M12 male connector</li> <li>1 x 8-pin M12 male connector</li> </ul>

For any other variants, please use the product enquiry form at the end of this data sheet or check the readily available article no. listed in the Bürkert eShop.



## 10.7. Ordering chart accessories

Description		Article no.
Display module, Type ME31		265468 
Blind cover in stainless steel 304/1.4301		265467 
	Unlocking magnetic key	690309 
<b>System Connect</b>		
<b>Type ME43 Gateway/Interface</b>		
bùS/Ethernet (PROFINET, EtherNet/IP, Modbus TCP, EtherCAT)		307390 
bùS/Profibus DP		307393 
<b>Type ME61 Display</b>		
Process View Display 3.5" (8.9 cm)		368544 
<b>EDIP Accessories</b>		
<b>bùS Stick Set</b>		
	USB-bùS-Interface Set 1, Type 8923. Detailed information can be found in chapter "9. Product accessories" on page 31.	772426 
USB-bùS Interface Set 2, Type 8923 (only bùS Stick, cable and bùS service cable)		772551 
<b>Connectors</b>		
5-pin M12 straight circular female connector for bùS		772416 
5-pin M12 straight circular male connector for bùS		772417 
5-pin M12 angled circular female connector for bùS		772418 
5-pin M12 angled circular male connector for bùS		772419 
bùS Y-distributor, 5-pin M12 circular female connector to 5-pin M12 circular male and 5-pin M12 circular connectors		772420 
bùS Y-distributor, 5-pin M12 circular female connector to 5-pin M12 circular male and 5-pin M12 circular connectors (power interrupt)		772421 
bùS adaptor M12 circular male connector A-coded - M12 circular male connector A-coded		772867 
bùS termination, 5-pin M12 circular male connector		772424 
bùS termination, 5-pin M12 circular female connector		772425 
Adaptor cable, 8-pin M12 circular female connector - 5-pin M12 circular male connector		773286 
<b>Connectors with cable</b>		
5-pin M12 angled circular female connector moulded on bùS cable, with open leads		0.7 m 772626 
5-pin M12 straight circular female connector moulded on bùS cable, with open leads		1 m 772409 
		3 m 772410 
		5 m 772411 
		10 m 772412 
Micro USB and 5-pin M12 straight circular male connector moulded on bùS cable		0.3 m 773254 
8-pin M12 straight female connector moulded on bùS cable, with open leads		2 m 919061 
<b>Extensions</b>		
	5-pin M12 straight circular female and male connectors moulded on bùS cable, shielded	0.1 m 772492 
		0.2 m 772402 
		0.5 m 772403 
		1 m 772404 
		3 m 772405 
		5 m 772406 
		10 m 772407 
		20 m 772408 
<b>Type 1573 Power Supplies</b>		
1 A (NEC Class 2 Power Units)		772361 
2 A (NEC Class 2 Power Units)		772362 
3.8 A (NEC Class 2 Power Units)		772898 
10 A		772698 

## 11. Product Enquiry Form - FLOWave SAW flowmeter

Thank you for your interest in our products! In order to provide you with optimum advice, please fill out the following form and send it to your **Bürkert representative** or e-mail address: [info@burkert.com](mailto:info@burkert.com). All information submitted will of course be kept strictly confidential.

Please fill in the **required fields!**  \*

\*Note: The interactive functions of this PDF may be restricted depending on the PDF reader used.

Personal Information			
<b>Company</b>		<b>Contact person</b>	
<b>Customer no.</b>		<b>Department</b>	
<b>Street</b>		<b>Country / Postcode / Town</b>	
<b>Telephone no.</b>		<b>Email</b>	

Delivery	
Quantity	Required delivery date

Operating data			
<b>Function</b> (Function of the flowmeter in the process / process description)			
<b>Type of medium</b>	Fluid		
<b>Process fluid</b>			
<b>Flow rate (Q)<sup>1.)</sup></b>	Min.	Max.	Unit
<b>Temperature</b>	Min.	Max.	Unit
<b>Absolute pressure</b>	Min.	Max.	Unit
<b>Viscosity</b>	Min.	Max.	Unit
<b>Density</b>	Min.	Max.	Unit

1.) Standardeinheit: Flüssigkeit Q = m<sup>3</sup>/h

Process connection					
<b>Pipe diameter DN</b>	08	15	25		
	40	50	65	80	
	3/8"	1/2"	3/4"	1"	
	1 1/2"	2"	2 1/2"	3"	
<b>Connection<sup>1.)</sup></b>	<b>Pipe DIN 11850</b>	Clamp DIN 32676 series A		Clamp DIN 11864-3 series A	
		Flange DIN 11864-2 series A			
		Thread DIN 11851 series A			
	<b>Pipe ISO 1127</b>	Clamp DIN 32676 series B		Clamp DIN 11864-3 series B	
		Flange DIN 11864-2 series B			
	<b>Pipe ASME BPE</b>	Clamp DIN 32676 series C		Clamp DIN 11864-3 series C	
		Flange DIN 11864-2 series C			
<b>Pipe SMS 3008</b>	SMS 3017				

1.) 3A & EHEDG certificate available (see restriction in certificate/certification specification in technical table)

Additional configuration			
<b>Surface finish (inner surface)</b>	Ra < 0.8 µm (30 µin.)		Ra < 0.4 µm (15 µin.) electro-polished
<b>FLOWave L Electrical connection</b>	Cable glands and M12 male connector (A-coded), in nickel plated brass (standard variant)	Cable glands and M12 male connector (A-coded), in stainless steel (Full stainless steel or ATEX/IECEX variants)	M12 female connectors (D-coded) and M12 male connector (A-coded) in stainless steel (Ethernet variant)
<b>FLOWave S Electrical connection</b>	5 pin M12 male connector (A-coded) in stainless steel (büS variant)		8 pin M12 male connector (A-coded) in stainless steel (variant with 2 configurable outputs (DO/AO))
<b>Display module</b>	With		Without
<b>Ethernet protocols</b>	Modbus TCP EtherNet/IP	PROFINET EtherCAT®	Without
<b>Option</b>	With density and massflow		Without density and massflow
<b>Special functions</b>	With differentiation factor (DF) With acoustic transmission factor (ATF)		Without differentiation factor (DF) Without acoustic transmission factor (ATF)
<b>Certification</b>	UL listed 1 + CULus	ATEX/IECEX	Without

**Note:**

If a certification which is not included in delivery with the FLOWave is requested, please order it separately. If you want to order one or more later, please contact your Bürkert office.

Certification	
<b>Included in delivery</b>	FDA certificate (included in delivery)
	Inspection certificate 3.1 acc. to EN 10204 (included in delivery)
	Certification of compliance ASME BPE (included in delivery)
	EHEDG - TYPE EL-CLASS I <sup>1.)</sup> (included in delivery)
	3A, 28-06 (included in delivery)
	Fluidic test report (test regarding volumetric flow rate or volume and mass flow rates, if density and mass flow rate option chosen)
<b>On order</b>	Calibration certificate for volume flow in water (2x3 points) (article no. 568114)
	Calibration certificate for volume flow, mass flow, density in water (2x3 points) (article no. 574229)
	USP class VI declaration
	ECR1935/2004 declaration
	CRN 0C21751 declaration
	Test report 2.2 acc. to EN 10204 (article no. 803722)
	Certification of conformity for the surface quality DIN 4762; EN ISO 4287; EN ISO 4288 (article no. 804175)
	Certification of conformity for passivation and electropolishing processes (article no. 444900)
	MTBF (Mean Time Between Failures) manufacturer declaration

1.) The EHEDG compliance is only valid if used in combination with gaskets from Combifit International B.V, Kieselmann GmbH, Germany or Siersema Komponenten Service (S.K.S.) B.V. according to the device variant.

Additional Requirements / Comment

DTS 1000270652 EN Version: U Status: RL (released | freigegeben | valide) printed: 12.07.2023

# Bürkert – Close to You

For up-to-date addresses  
please visit us at  
[www.burkert.com](http://www.burkert.com)

DTS 1000270652 EN Version: U Status: RL (released | freigegeben | validé) printed: 12.07.2023

Austria  
Belgium  
Czech Republic  
Denmark  
Finland  
France  
Germany  
Italy  
Netherlands

Norway  
Poland  
Spain  
Sweden  
Switzerland  
Turkey  
United Kingdom

